
IceWarp Unified Communications

php.user.ini

Version 12



Published on 3/6/2017

php.user.ini Usage

IceWarp Server uses the **php.ini** file. This file is used for storing of php settings.

After every server upgrade, this file is overwritten. It means that any changes performed before upgrade are lost. It can be annoying to do these changes again and again. To ease your work, you may want to use the **php.user.ini** file.

When placed in the same folder as the **php.ini** file, content of the **php.user.ini** file is attached automatically to the **php.ini** one during server upgrade. The later occurrence of the same setting is used.

This means that you can insert all changes performed against the original **php.ini** file into the **php.user.ini** one that is not overwritten during upgrade and the server will use these changed settings.

Example

Part of the original **php.ini** file:

```
...
extension=php_pdo_odbc.dll
;extension=php_pdo_mysql.dll
;extension=php_mysql.dll
;zend_extension_ts = "ext\php_xdebug.dll"

;extension=php_bz2.dll
;extension=php_ctype.dll
;extension=php_cpdf.dll
;extension=php_curl.dll
...
```

Part of the **php.user.ini** file:

```
...
extension=php_pdo_mysql.dll
extension=php_bz2.dll
...
```

Part of the **php.ini** file after upgrade:

```
...
extension=php_pdo_odbc.dll
;extension=php_pdo_mysql.dll
;extension=php_mysql.dll
;zend_extension_ts = "ext\php_xdebug.dll"

;extension=php_bz2.dll
;extension=php_ctype.dll
;extension=php_cpdf.dll
;extension=php_curl.dll
...
extension=php_pdo_mysql.dll
extension=php_bz2.dll
...
```

The uncommented ***extension=php_bz2.dll*** setting is used because of its later occurrence.php